## DECLARATION OF PERFORMANCE

## INTCO20240126

- Unique identification code of the product-type: PVC Wall Panel (Length\*Width \* thickness: 2400mm\*600mm\*8mm)
   Intended use/es:
- internal finishes of walls, partitions and ceilings under system 4
  Manufacturer:
  - Shanghai Intco Industries Co., Ltd.
- 4. Contact address of the manufacturer: No.1299 Hubin Road, Fengxiian District, Shanghai, China
- 5. System/s of AVCP: System 4
- 6. Harmonised standard: EN 15102:2007+A1:2011
- 7. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Classification	Project	Reference standard	Standard	Result	Conclusion
Physical Properties	Density	-	-	1.1 g/cm <sup>3</sup>	-
	Vicat softening temperature	-	-	88.5°C	-
	Shore hardness	-	-	57.5HD	-
Durability	Water absorption	EN 317:1993	-	the average value is 0.0%	-
	Peel test		≥40N	47N	Pass
Thermal Performance	Thermal Resistance	EN 15102:2007+A1:2011 EN 12667:2001	-	0.074m <sup>2</sup> • K/W	-
	Fire Resistance	GB 8624-2012 GB/T 20284-2006 GB/T 8626-2007	-	GB 8624 B1(C- s3, d0)	B1
Safety	Heavy metals	EN 15102:2007+A1:2011	As:<500mg/kg Ba:<25mg/kg Cd:<60mg/kg Cr:<90mg/kg Hg:<20mg/kg Pb: No upper limit Sb:<25mg/kg Se:<165mg/kg	not detected	Pass
	Formaldehyde Release	EN 15102:2007+A1:2011 EN 12149:1997	<120 mg/kg	not detected	Pass

Signed for and on behalf of the manufacturer by:

2024-1-12

(place and date of issue)

(signature)